



Specifications

Varibeam code 192 800W - **code 212** 1000W - 120/240V
yoke mount
kg.1,410

Varibeam code 190 800W - **code 210** 1000W - 120/240V
clamp + jointed arm mount
kg.1,554

Extra-pure aluminium reflector; diffusing finish
Lampholder cup matt black finished
Lampsocket type R7s
Spot-flood rear knob
Power cable 3,50 m. long. Section 3x1,5 mmq
CEI 20-35 Flame retardant Fire resistant
In-line switch 8 Amp. 250V (16 Amp. 125V) with fibre glass protective housing.
Yoke mount in aluminium with 5/8" (16mm) socket
Clamp mount in fibre glass with hinged arm.

Accessories

Code 118: CE 200 gr. Wire guard with holder ring for barndoors and other accessories.
Integrated to CE fixtures.

Code 802: 380 gr. Four leaf barndoor + gel clips

Code 801: 435 gr. Four leaf barndoor/wire guard assembly + gel clips

Code 183: 440 gr. Accessory holder

Accessories to be fitted in accessory holder 183:

Code 195: 20 gr. Wire guard

Code 803: 180 gr. Safety glass

Code 805: 180 gr. Diffuser glass

Code 184: 180 gr. Dichroic daylight filter

Code 185: 25 gr. Double scrim

Code 186: 20 gr. Single scrim

Code 187: 20 gr. Half double scrim

Code 189: 30 gr. Half single scrim

Code PHO WD: Medium White dome

Code 182: 550 gr. Umbrella diam. 100

Code M026: 350 gr. Umbrella universal adapter lite-tite

Code 301: Maxi Alu stand (compact 052)

Code 106: Mini Pro Alu stand (Minipro 051N)

Code 327: Gag grip with 5/8" (16mm) spigot

Photometrics

DISTANCE 5 m (800w DXX)	SPOT	FLOOD
light center value	1235	445
beam angle= beam at 50% peak value	36°30'	69°
field angle= beam at 10% peak value	90°	129°
RATIO	1:2.78	

Fitting halogen lamps with R7s base.

Long 80mm: 800w P2/13 DXX - 600w L598 - 500w L600

Long 93mm: 1000w P2/35 13704 - 800w L603 - 600w L604



CODE 190 / 210



CODE 192 / 212